Website: www.minsu.edu.ph

Email: universitypresident@minsu.edu.ph Mobile: +63 977 846 72 28 **BAGONG PILIPINAS** 

# **REQUEST FOR QUOTATION**

SUPPLY AND DELIVERY OF SEMI-EXPENDABLE ICT EQUIPMENT AND OTHER SUPPLIES AND MATERIALS FOR THE MIS OFFICE OF MINSU MAIN **CAMPUS** 

PR No.: PR25-0035 RFQ No. 2025-033 ABC Amount: Php296,664.00

Lot 1: Php190.680.00

	LOC 1. F119130,080	2.00
	Lot 2; Php105,98	4.00
Compa	ompany Name :	
Addres	ddress :	
	Please quote your lowest price on the items / listed below, subject to the General Condition on the last page	, stating the shortest time of
deliver	elivery and submit your quotation duly signed by your representative not later than in the ad-	dress stated in the last page.
	CIEDELLE PIOL-	SALAZAR, J.D., Ph.D.
	BAC C	Chairperson
Note:	te: 1. All entries must be typewritten.	
	2. Delivery Period withincalendar days.	
	3. Warranty shall be for a period of six (6) months for supplies and materials, one (1) year for Equipment, from date	
	of acceptance by the procuring entity.	
	4. Price validity shall be a period of 30 calendar days.	

 ${\bf 5.}\ \ {\bf G\text{-}EPS}\ Registration\ Certificate\ shall\ be\ attached\ upon\ submission\ of\ the\ Quotation.$ 6. Bidders shall submit Original Brochures showing certification of the product being offered (optional).

7. Mode of delivery: [ ] Pick-up (Schedule) [ ] Door to Door Delivery

Item No.	Unit	ITEM AND DESCRIPTION	QTY.	UNIT PRICE	TOTAL AMOUNT
		LOT 1- SEMI-EXPENDABLE ICT EQUIPMENT			
		EXPENSES			
1	unit	UNINTERRUPTIBLE POWER SUPPLY	6		
		Input Voltage 230VAC			
		Frequency 50hz – 60hz (auto sensing)			
		Voltage Range 140 - 300VAC			
		Capacity VA/Wattage 4KVA/2800W			
		Transfer Time 4 – 8 ms (typical)			
		Power Cord Length 1.2meter			
		Outlet Socket back-up x8, total of 8 sockets			
		Back up time 6 – 30mins depending on computer			
		load			
2	unit	WIRELESS ROUTER	5		
		Wireless Protocol			
		Wi-Fi 6, 2976Mbps			
		Antenna			
		5 External 5 dBi Antennas			
		Max/Recommended Clients (Wi-Fi)			
		160/80			
		Recommended Total Clients (LAN+Wi-Fi)			
		160			
		MIMO			
		2x2 @2.4 GHz, 2x2 @5 GHz			
		Network Interface			
		5 x 10/100/1000 Base-T			
		Max. WAN Ports			
		4, 10/100/1000 Base-T			
		CPU			
		Dual Cores, 1.3GHz			

MSU-BAC-FR-05.01

Email: universitypresident@minsu.edu.ph Website: www.minsu.edu.ph Mobile: +63 977 846 72 28



		RAM			
		512MB			
		Recommended Bandwidth from ISP			
		1.2Gbps			
		Dimension			
		283 mm × 172 mm × 46 mm (without antennas)			
		Power Supply			
		100V~240V AC, 50/60Hz			
3	unit	POINT TO POINT ANTENNA	10		
		Mechanical:			
		Dimensions: 358 × 271.95 × 272.5 mm			
		Material: Reflector (SGCC 0.6T), Plastic			
		Mounting: Pole-mounting kit included			
		Wind Survivability: 200 km/h (125 mph)			
		Hardware:			
		Networking: 1× Gigabit Ethernet port			
		Power: Passive PoE (adapter included)			
		Power Consumption: Max 7W			
		Gain: 23 dBi			
		Processor: MIPS 74Kc			
		Memory: 64 MB DDR2			
		Channel Sizes:			
		PtP: 10/20/30/40/50/60/80 MHz			
		PtMP: 10/20/30/40 MHz			
4	unit	FUSION MACHINE	1		
	unit		_		
	unic	Fiber alignment: Core/cladding alignment /			
	unit		<del>_</del>		
	unic	Fiber alignment: Core/cladding alignment /			
	unit	Fiber alignment: Core/cladding alignment / Manual alignment	<del>-</del>		
	unit	Fiber alignment: Core/cladding alignment / Manual alignment Splicing time: 5S			
	unit	Fiber alignment: Core/cladding alignment / Manual alignment Splicing time: 5S Heating time: 15S Automatic heating(Preheating)			
	unit	Fiber alignment: Core/cladding alignment / Manual alignment  Splicing time: 5S  Heating time: 15S Automatic heating(Preheating)  Construction Lighting: Built in high brightness,			
	unit	Fiber alignment: Core/cladding alignment / Manual alignment  Splicing time: 5S  Heating time: 15S Automatic heating(Preheating)  Construction Lighting: Built in high brightness, wide range of lights, easy to operate at night			
	unit	Fiber alignment: Core/cladding alignment / Manual alignment  Splicing time: 5S  Heating time: 15S Automatic heating(Preheating)  Construction Lighting: Built in high brightness, wide range of lights, easy to operate at night  Screen: 5 inch TFT Display			
	unit	Fiber alignment: Core/cladding alignment / Manual alignment  Splicing time: 5S  Heating time: 15S Automatic heating(Preheating)  Construction Lighting: Built in high brightness, wide range of lights, easy to operate at night  Screen: 5 inch TFT Display  Focus mode: Six motors Auto focus			
		Fiber alignment: Core/cladding alignment / Manual alignment  Splicing time: 5S  Heating time: 15S Automatic heating(Preheating)  Construction Lighting: Built in high brightness, wide range of lights, easy to operate at night  Screen: 5 inch TFT Display  Focus mode: Six motors Auto focus  Splice Loss:			
		Fiber alignment: Core/cladding alignment / Manual alignment  Splicing time: 5S  Heating time: 15S Automatic heating(Preheating)  Construction Lighting: Built in high brightness, wide range of lights, easy to operate at night  Screen: 5 inch TFT Display  Focus mode: Six motors Auto focus  Splice Loss:  0.025dB (SM), 0.01dB(MM) 0.04dB (DS/NZDS)			
		Fiber alignment: Core/cladding alignment / Manual alignment  Splicing time: 5S  Heating time: 15S Automatic heating(Preheating)  Construction Lighting: Built in high brightness, wide range of lights, easy to operate at night  Screen: 5 inch TFT Display  Focus mode: Six motors Auto focus  Splice Loss:  0.025dB (SM), 0.01dB(MM) 0.04dB (DS/NZDS)  Power:			
		Fiber alignment: Core/cladding alignment / Manual alignment  Splicing time: 5S  Heating time: 15S Automatic heating(Preheating)  Construction Lighting: Built in high brightness, wide range of lights, easy to operate at night  Screen: 5 inch TFT Display  Focus mode: Six motors Auto focus  Splice Loss:  0.025dB (SM), 0.01dB(MM) 0.04dB (DS/NZDS)  Power:  Input AC100-240V 50 / 60HZ, Output DC13.5V /			
		Fiber alignment: Core/cladding alignment / Manual alignment  Splicing time: 5S  Heating time: 15S Automatic heating(Preheating)  Construction Lighting: Built in high brightness, wide range of lights, easy to operate at night  Screen: 5 inch TFT Display  Focus mode: Six motors Auto focus  Splice Loss:  0.025dB (SM), 0.01dB(MM) 0.04dB (DS/NZDS)  Power:  Input AC100-240V 50 / 60HZ, Output DC13.5V / 4.8A			
		Fiber alignment: Core/cladding alignment / Manual alignment  Splicing time: 5S  Heating time: 15S Automatic heating(Preheating)  Construction Lighting: Built in high brightness, wide range of lights, easy to operate at night  Screen: 5 inch TFT Display  Focus mode: Six motors Auto focus  Splice Loss:  0.025dB (SM), 0.01dB(MM) 0.04dB (DS/NZDS)  Power:  Input AC100-240V 50 / 60HZ, Output DC13.5V / 4.8A			
		Fiber alignment: Core/cladding alignment / Manual alignment  Splicing time: 5S  Heating time: 15S Automatic heating(Preheating)  Construction Lighting: Built in high brightness, wide range of lights, easy to operate at night  Screen: 5 inch TFT Display  Focus mode: Six motors Auto focus  Splice Loss:  0.025dB (SM), 0.01dB(MM) 0.04dB (DS/NZDS)  Power:  Input AC100-240V 50 / 60HZ, Output DC13.5V / 4.8A  Applicable Fibers:  SM(G.652&G.657);MM(G.651);DS(G.657);NZDS(G.655)			
		Fiber alignment: Core/cladding alignment / Manual alignment  Splicing time: 5S  Heating time: 15S Automatic heating(Preheating)  Construction Lighting: Built in high brightness, wide range of lights, easy to operate at night  Screen: 5 inch TFT Display  Focus mode: Six motors Auto focus  Splice Loss:  0.025dB (SM), 0.01dB(MM) 0.04dB (DS/NZDS)  Power:  Input AC100-240V 50 / 60HZ, Output DC13.5V / 4.8A  Applicable Fibers:  SM(G.652&G.657);MM(G.651);DS(G.657);NZDS(G			
		Fiber alignment: Core/cladding alignment / Manual alignment  Splicing time: 5S  Heating time: 15S Automatic heating(Preheating)  Construction Lighting: Built in high brightness, wide range of lights, easy to operate at night  Screen: 5 inch TFT Display  Focus mode: Six motors Auto focus  Splice Loss:  0.025dB (SM), 0.01dB(MM) 0.04dB (DS/NZDS)  Power:  Input AC100-240V 50 / 60HZ, Output DC13.5V / 4.8A  Applicable Fibers:  SM(G.652&G.657);MM(G.651);DS(G.657);NZDS(G .655)  sub-TOTAL Lot 1  LOT 2- OTHER SUPPLIES AND MATERIALS			
		Fiber alignment: Core/cladding alignment / Manual alignment  Splicing time: 5S  Heating time: 15S Automatic heating(Preheating)  Construction Lighting: Built in high brightness, wide range of lights, easy to operate at night  Screen: 5 inch TFT Display  Focus mode: Six motors Auto focus  Splice Loss:  0.025dB (SM), 0.01dB(MM) 0.04dB (DS/NZDS)  Power:  Input AC100-240V 50 / 60HZ, Output DC13.5V / 4.8A  Applicable Fibers:  SM(G.652&G.657);MM(G.651);DS(G.657);NZDS(G .655)  sub-TOTAL Lot 1  LOT 2- OTHER SUPPLIES AND MATERIALS  EXPENSES			
	pcs	Fiber alignment: Core/cladding alignment / Manual alignment  Splicing time: 5S  Heating time: 15S Automatic heating(Preheating)  Construction Lighting: Built in high brightness, wide range of lights, easy to operate at night  Screen: 5 inch TFT Display  Focus mode: Six motors Auto focus  Splice Loss:  0.025dB (SM), 0.01dB(MM) 0.04dB (DS/NZDS)  Power:  Input AC100-240V 50 / 60HZ, Output DC13.5V / 4.8A  Applicable Fibers:  SM(G.652&G.657);MM(G.651);DS(G.657);NZDS(G .655)  sub-TOTAL Lot 1  LOT 2- OTHER SUPPLIES AND MATERIALS EXPENSES  THERMAL PASTE	6		
		Fiber alignment: Core/cladding alignment / Manual alignment  Splicing time: 5S  Heating time: 15S Automatic heating(Preheating)  Construction Lighting: Built in high brightness, wide range of lights, easy to operate at night  Screen: 5 inch TFT Display  Focus mode: Six motors Auto focus  Splice Loss:  0.025dB (SM), 0.01dB(MM) 0.04dB (DS/NZDS)  Power:  Input AC100-240V 50 / 60HZ, Output DC13.5V / 4.8A  Applicable Fibers:  SM(G.652&G.657);MM(G.651);DS(G.657);NZDS(G .655)  sub-TOTAL Lot 1  LOT 2- OTHER SUPPLIES AND MATERIALS  EXPENSES			

Email: universitypresident@minsu.edu.ph Website: www.minsu.edu.ph Mobile: +63 977 846 72 28



		150Mbps Wireless N Nano USB Adapter			
3	pcs	CABLE MANAGER	8		
	рез	Rack Mounted 19 inches			
4	box	INDOOR UTP CABLE	4		
4	DUX	CAT6 UTP	- 4		
		Ethernet LAN Network Cable 305M/Box			
5	roll	OUTDOOR UTP LAN CABLE	3		
J	1011	Category: Cat 6 Ethernet cable	<u> </u>		
		Cable Type: Unshielded Twisted Pair			
		Color: Black			
		Length: 305 meters (per roll).			
		Physical and Technical Details:			
		Conductor Size: 24 AWG			
		Jacket Material: Durable PVC			
		Data Transfer Speed: Up to 1 Gbps.			
6	unit	Bandwidth Support: Up to 250 MHz.			
6	unit	DATA CABINET  Wallmounted Data Cabinet	5	1	
		Size: 6U/ 6-Layer/ 1FT Height Dimension: W600 x D450mm x H=1FT			
		Removable Side Panels			
		Single swing detachable front tempered glass door with keylock			
7	unit	LAN TESTER	6		
/	unit	Key Functions:	0		
		Tests UTP/STP, RJ45, RJ11 cables.			
		Detects miswiring, open/short circuits			
		, and cable disorders.			
		Remote testing up to 1000 ft			
		Tone signal detection for cables			
8	pcs	ELECTRICAL TAPE	15		
0	pcs	Black 19mm × 16mm × 16m	13		
9	unit	SURGE PROTECTOR	12		
,	unit	Multi-Stage Protection: Offers high protection for	12		
		equipment.			
		Fast Response: Built-in semiconductor			
		Low Capacitance Design: Superior transmission			
		performance.			
		transmission distances.		†	
		Lightning Protection: Prevents induced lightning		†	
		surges and protects equipment from lightning		+	
		strikes.			
		Supports Non-Standard POE Switches:		1	
		Compatible with various POE devices,		1	
10	box	NAIL CLIP	6	1	
	2011	PVC Cable Clip Round 4mm (100Pcs)		1	
11	box	NAIL CLIP	6		
		PVC Cable Clip Round 6mm (100Pcs)	-	1	
		1		1	

Email: universitypresident@minsu.edu.ph Website: www.minsu.edu.ph Mobile: +63 977 846 72 28



12	unit	SPLICE TOOL KIT FIBER OPTIC	3		
		Size of fiber cutter:61*64*55mm			
		Suitable for bare fiber diameter: 125mm			
		Applicable fiber core number: single core			
		Applicable fiber coating diameter: 0.25 & 0.9mm			
		Stripping length before fiber cutting:			
		fiber cutting length +18mm or more			
		Optical fiber cutter length:			
		9-16mm (0.25mm) 10-16mm (0.9mm)			
		Cutting angle representative value: ≤ 0.5°			
		Blade life: 48000 core wire			
	•	Esub-TOTAL Lot 2	•		
XV	XVXVXVXVX	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	XVXVXVX	xvx	
	<u> </u>		TOTAL		

After having carefully read and accepted your General Condition, I / We quote you on the item at prices noted above

Supplier's Signature over Printe	ed Name
TIN No. of Establishment	
Contact Number	
Date	

Email: universitypresident@minsu.edu.ph Website: www.minsu.edu.ph

Mobile: +63 977 846 72 28



#### **General Conditions**

- 1. Quotations and other requirements stated below shall be submitted to the Bids and Awards Committee (BAC) Office, Mindoro State University -Main Campus, Alcate, Victoria, Oriental Mindoro, Philippines on the date and time stated in this RFP.
- 2. Supplier shall submit the following requirements:
  - a. Duly signed original copy of Request for Quotation (RFQ). Prices shall be quoted in Philippine Pesos.
  - b. PhilGEPS Registration
  - c. Valid Mayor's/Business Permit
  - d. Omnibus Sworn Statement
  - e. BIR Certificate of Registration
  - f. Latest Income/Business Tax Return
  - g. TAX Clearance
  - h. DTI Registration/SEC Certificate
  - i. Original Brochures or certificates of the items offered showing its performance characteristics or specifications, if applicable

Price validity shall be 30 calendar days from the deadline of submission of quotation.

#### Ocular Inspection

Upon the decision of the End-User and BAC, the supplier and its concerned premises may be subjected to ocular inspection and approval by the End-User and/or TWG Inspections of the BAC prior to the award.

#### Award

The supplier that submitted the lowest calculated responsive quotation, and passed the inspection conducted by the End-User and BAC prior to the event, if any, shall be awarded the contract.

### **Evaluation of Quotations**

Quotations shall be compared and evaluated of the basis of the following criteria:

- 1. Completeness of Submission
- 2. Compliance with Item & Description Requirements
- 3. Price

### Instructions

- 1. Supplier shall be responsible for the source(s) of its goods/services/equipment, and which shall be in accordance with the schedule and specifications of the RFQ or contract. Failure of the supplier to comply with this provision shall be ground for cancellation of the award or purchase order issued to the supplier.
- Supplier that accepted an award, purchase order, or contract but failed to deliver the required goods/services/equipment within the time called for in the award, purchase order, or contract shall be disqualified from participating in MinSU or any of MinSU campuses future procurement activities. This is without prejudice to the imposition of other sanctions prescribed under R.A. 9184 and its IRR-A against the supplier.
- All duties, excise, and other taxes and revenue charges shall be paid by the supplier.
- All transactions are subject to withholding of credible Government Taxes per revenue regulation(s) of the Bureau of Internal Revenue

## Liquidation Damages

A penalty of one-tenth of one percent (0.001) of the total value of the undelivered goods/services/equipment shall be charged as liquidated damages for every day of delay of the delivery of the purchased goods/services/equipment.

### Warrantv

Supplier warrants that all goods/services/equipment to be provided are of acceptable industry standard.

### **Payment**

Payment shall be made only upon a certification by the Head of the Procuring Entity to the effect that the GOODS have been rendered or delivered in accordance with the terms of this Contract and have been duly inspected and accepted.